

Problem E

Finding Bottleneck Shortest Paths

Input File: *pe.in*
Time Limit: *1 second*

Problem Description

A sensor network consists of a set of n sensors s_1, s_2, \dots, s_n . All the sensors are placed in a two dimensional plane and will never be moved again. Thus, each sensor s_i has a fixed coordinates (x_i, y_i) .

A pair of sensors s_i and s_j can communicate by sending messages. Suppose that s_i wants to send a message directly to s_j , a fixed amount of electrical power $p_{i,j}$ is required at s_i . In real world situation, the value of $p_{i,j}$ depends on many factors. For simplicity we assume that the value of $p_{i,j}$ depends only on the distance between the communicating sensors. In this problem, we assume that

$$p_{i,j} = (x_i - x_j)^2 + (y_i - y_j)^2.$$

Furthermore, we assume that only the sender needs to consume this amount of power in the communication.

Since the power stored in each sensor is a precious resource, sending message directly to the destination sensor may consume too much electrical power for a sensor. In this problem, we want to find an *optimal* path to send a message from s_i to s_j such that the maximum power required by the sensors on the path is minimized.

More formally, let P be a *valid* path from s_i to s_j . Let $k_1 = i, k_2, \dots, k_r = j$ be the sequence of the indexes of the sensors along the path P . Define the weight of P by

$$w(P) = \max_{1 \leq i < r} \{p_{k_i, k_{i+1}}\}.$$

A path P is an optimal path from s_i to s_j if its weight $w(P)$ is minimized among all paths from s_i to s_j .

Given a sensor network G , the sender s_i and the receiver s_j , write a program to compute an optimal path from s_i to s_j for sending a message.

Input Format

An instance of the problem consists of

1. the number of sensors n ,
2. the coordinates of the sensors (x_i, y_i) , $1 \leq i \leq n$, and
3. the source and the destination sensors s_i and t_i .

These data are stored in $\lceil n/20 \rceil + 2$ lines in the input file.

1. The first line is the integer n .
2. The following $\lceil n/20 \rceil$ lines are the n coordinates (x_i, y_i) , $1 \leq i \leq n$. Each line contains at most 20 coordinates. Each coordinates is written in two numbers x_i and y_i , without the parentheses.

3. The last line of an instance contains two integer i and j , indicating s_i is the sender and s_j is the receiver.

In this problem, we assume that $1 < n < 1000$, x_i and y_i are integers and $0 \leq x_i, y_i < 2^{15}$.

Note that the test data file may contain more than one instances. The last instance is followed by a line containing a single 0.

Output Format

The output for each test case is an integer w which is the maximum power required along the optimal path from s_i to s_j .

Sample Input

```
4
0 0 1 9 8 2 10 10
1 4
5
0 0 8 2 3 4 8 7 10 10
1 5
0
```

Sample Output

```
68
29
```